

MAXIMA 250



**TECNO
INCOLLAGGI**

Melting unit for Hot Melt adhesives
Applicatori per adesivi termo-fusibili

MAXIMA 250

*Traditional and reactive hot melt adhesive applicators
mod. MAXIMA 250*

Dimensions	1940x1160x1430 mm
Tank capacity	250 l
Melting capacity*	600 kg/h
Electrical power	50 kW
Tension	400 V+N+G

* Varied according to adhesive's type

MAXIMA 250 has been developed to supply any kind of adhesives: EVA, polyolefin, polyamide, or rubber.

MAXIMA 250 can be fed in automatically. MAXIMA 250 is suitable for manual, automatic and spray mode.

Several options (additional grids) are available according to the adhesive's type.

*Applicatore per hot melt
mod. MAXIMA 250*

Dimensioni	1940x1160x1430 mm
Capacità vasca	250 lt
Capacità di fusione*	600 kg/ora
Potenza	50 kW
Tensione	400 V+N+T

* Variabile secondo il tipo di adesivo

Gli applicatori MAXIMA 250 sono stati progettati per l'applicazione di qualsiasi tipo di adesivo: EVA, poliolefinico, poliammidico, o gomma.

MAXIMA 250 può essere caricata in automatico. MAXIMA 250 può funzionare in modo manuale, automatico e spray.

Parecchie opzioni sono disponibili secondo il tipo di adesivo.

STANDARD FEATURES

- Tank with teflon coating
- Microprocessor for temperature control up to 250°C with weekly program for automatic pre ignition
- Economy function
- Gear pump with safety valve
- 2 or 8 grids available
- Structure in painted welded steel
- Hermetic lid
- Pre equipped for 4 tubes and 4 heads

CARATTERISTICHE STANDARD

- Vasca teflonata
- Microprocessore per controllo temperature fino a 250°C con preaccensione settimanale per ogni canale
- Funzione economy
- Pompa ad ingranaggi con valvola di sicurezza
- 2 o 8 griglie disponibili
- Struttura in acciaio verniciato
- Coperchio a tenuta ermetica
- Collegamento con 4 tubi e 4 teste



Testa di spalmatura RTS
Spreading head RTS



Caricamento automatico da fusti
Automatic drum loading



Caricamento automatico granuli
Automatic granulates loading system



TECNO INCOLLAGGI
ADHESIVE TECHNOLOGY AND AUTOMATION

TECNO INCOLLAGGI s.r.l.

24050 Zanica (BG) Italy - Via Borsellino Zona indust. N° 5

Tel. +39 035/670.729 • Fax +39 035/675.628

web: www.tecnoincollaggi.com • e-mail: info@tecnoincollaggi.com